UCC 548-T UCC 548-TR

All-round high feeder jacquard model for all kinds of transfer and textured textiles

The UCC 548-T is an all-rounder and creates functional leisure and sportswear, while offering a flexible production and great design versatility. The model features a wide variety of applications while producing single and double jersey combinations in addition to hole pattern and textured structures.

The UCC 548-T is easily convertible to the UCC 548-TR and offers enormous pattern possibilities in the production of fashionable textiles through specially designed stitch-forming edges.

- Excellent fine gauge transfer technology
- Flexible and productive knitting machine with 1.6 feeds per inch
- Flexible production of leisure and sportswear
 - Body Mapping technology
 - Numerous pattern options

Terrot GmbH Paul-Gruner-Straße 72 b 09120 Chemnitz GERMANY Phone: +49 371 5201-0 Fax: +49 371 5201-200 Email: info@terrot.de www.terrot.de





UCC 548-T UCC 548-TR

All-round high feeder jacquard model for all kinds of transfer and textured textiles

The UCC 548-T is a highly flexible knitting machine featuring transfer technology for the production of functional sports and leisurewear.

Advantages at a glance

- Made in Germany maximum efficiency and precision
- High production of fine gauge transfer fabrics up to E24 in cylinder and dial with 1.6 feeds per inch
- Also available in different gauge settings in cylinder (E14 or E16) and dial cam (E28 or E32)¹ for more application possibilities
- Combines single and double jersey to boost features like breathability, stretch and fit
- Creates sportswear with an improved fit called Body Mapping
- Using 3-way technology in cylinder needle selection for knit, tuck and miss
- Reliable and high quality elastane plating
- Easily convertible to the UCC 548-TR for a higher level of fashionable fabrics and a greater pattern diversity
- Reliable needle selection for numerous pattern options with Terrot's new pattern software "Paint Terrot"

Model	UCC 548-T	UCC 548-TR			
Diameter [inch]	30, 34				
Feeders per inch	1.6				
Gauges [E]	6 – 24	10 – 20			
Fine Gauge ¹	14/28 or 16/32				
Speed up to [rpm]	18				
Speedfactor [max]	540 SF				
Knitting technology	Electronically controlled, elastane plating, individual needle selection				
Possible structures	Transfer jacquard, relief				
Fabric application	Leisure and sportswear, outerwear				

Transfer pattern production example of the UCC 548-T for 34 inch and 16 rpm [unfinished, 85 %]

Exemplary fabric application	Gauge [E]	Yarn	Weight [g/m²]	Production [m/h]	Production [kg/h]
Leisure wear	16	Co Nm 34/1	140	32.27	9.57
Sports and leisure wear	14/28 ¹	PES "COOLPLUS" Nm 50/1	130	20.98	6.27
Sportswear	24	PES 100 den, Elastan 20 den	155	16.32	5.10

Technical details

Relief pattern production example of the UCC 548-TR for 34 inch and 16 rpm [unfinished, 85 %]

Exemplary fabric application	Gauge [E]	Yarn	Weight [g/m²]	Production [m/h]	Production [kg/h]
Fashionable outerwear	16	PES 110 dtex, PES 240 dtex	165	25.92	8.72
Fashionable outerwear	16	Co Nm 50/1	190	17.65	7.36