



# | I3P184 | I3P284 | I3P284-1

Terrot I3P 8-lock machines provide universal application options, coupled with maximum flexibility

# Frame

- Standard C-frame for 500 mm fabric rolls	•
- Gauge conversion "Quick Change"	•
- Central dial height adjustment	•
Oil both for dial drive and a linder bearing	_

Oil bath for dial drive and cylinder bearing
 Hand levers

- Uniwave spray oiler
- Industrial C-frame for 800 and 1050 mm fabric rolls
- Pulsonic 5 oiler
o

# Needles

- 2+2 needle tracks in dial and cylinder (I3P284)	
- 2+4 needle tracks in dial and cylinder	

(I3P184 | I3P184-1) • Range of delayed timing max. 5,5 mm • o

#### Cam Parts

- Exchange cam for 3-Way-Technique KNIT-TUCK-MISS and SUPPORT

#### Fabric take-down

- Motorized fabric take-down with 3-roller	
--	--

- Automatic winding up device

Segmented take-down shaftCadratex fabric spreader

- Fabric folding device

- Fabric basket

- Rotating cutting device

# Yam feeding

- 2 rings, 4 step drives
- Positive feeding unit type MPF
- Ceramic yarn carriers
- Standard tube creel
- Elastomeric plating equipment with MER
- Various creel versions

### Electric

- Frequency controlled drive (AC) 4 KW
- Control voltage 24 V

# Control

- Terrot Control
- 5-shift counter
- Digital revolution counter
- Fabric roll size counter
- BDE interface

# Additional

- Needle bed lighting
- Venticleaner
- Electronic needle detectors
- Spacer fabric conversion kit
- Yarn carrier for lay-in
- Latch opener for cylinder needles

Туре	I3P184				
Diameter in inch	30"	34"	36"	38"	40"*
No. of feeders	84	96	100	106	112
Gauges E	18 – 36				
Needle tracks	2 + 4 in dial and cylinder				

Туре	I3P284					
Diameter in inch	30"	32"	34"	36"	38"	40"
No. of feeders	84	90	96	100	106	112
Gauges E	18 – 36					
Needle tracks	2 + 2 in dial and cylinder					

Туре	I3P284-1				
Diameter in inch	30"	34"	42"		
No. of feeders	84	96	120		
Gauges E	18 – 50				
Needle tracks	2 + 2 in dial and cylinder				

\*on request

0

0

0

0



13P284 - knitting head



13P184 - 2+4 cam tracks



13P284 - 2+2 cam tracks

Standard Options
 Frontpage: machine model I3P284

Subject to technical changes. Illustrations may show accessories that are not included in the standard version. Program update 10/2015

Terrot GmbH Paul-Gruner-Straße 72B 09120 Chemnitz Germany

Phone: +49 371 5201-0 | Fax: +49 371 5201-200

email: info@terrot.de | www.terrot.de