



SH124 | SH130 | SBF124 | SBF130

Terrot Single-Jersey body size machines provide most advanced technology to produce high-quality seamless knits

Frame

- Gauge conversion "Quick Change"
- Central and individual stitch length adjustment
- Oil bath for cylinder bearing
- Hand levers
- Uniwave spray oiler
- Industrial C-frame for 800 and 1050 mm fabric rolls o
- Pulsonic 5 oiler

Needles

- Up to 2 types of cylinder needles
- Up to 4 types of cylinder needles

Cam parts

- Exchangeable cam for 3 positions in KNIT-TUCK-MISS (2 needle tracks)
- Conversion kit for 3-Thread-Fleece fabric (SBF124 | SBF130)

Fabric take-down

- Motorized fabric take-down with 3-roller

0

0

0

- Segmented take down shaft
- Automatic winding up device
- Cadratex fabric spreader
- Fabric folding device
- Fabric basket
- Rotating cutting device

Yarn feeding

- 2 rings, 4 step drives
- Positive feeding unit type MPF
- Ceramic yarn carriers
- Standard tube creel
- Elastomeric plating equipment with MER
- Various creel versions

Electric

- Frequency controlled drive (AC) 4 KW
- Control voltage 24 V

Control

- Terrot Control
- Central processor unit with display
- 5-shift counter
- Digital revolution counter
- Fabric roll size counter
- BDE interface

Additional

- Needle bed lighting
- Venticleaner
- Electronic needle detectors
- Standard Options

Туре	SH ⁻	124	SBF124				
Diameter in inch	30"	34"	30"	34"			
No. of feeders	72	82	72	82			
Gauges E	18 -	- 36	16 -	- 20			

Туре	SH130													
Diameter in inch	9"	10"	11"	12"	13"	14"	15"	16"	17"	18"	19"	20"	21"	22"
No. of feeders	27	30	33	36	39	42	45	48	51	54	57	60	63	66
Gauges E	12 – 28													

Туре	SH130									
Diameter in inch	23"	23" 24" 26" 28" 30" 32" 34"								
No. of feeders	69	72	78	84	90	96	102	108		
Gauges E	12 – 28									


Туре	SBF130								
Diameter in inch	16"	17"	18"	19"	20"	21"	22"	23"	24"
No. of feeders	48	51	54	57	60	63	66	69	72
Gauges E	16-20								



SH130 - knitting head



SH130 – sinker cam and cylinder cam



SBF130 - sinker cam and cylinder cam 3-Thread-Fleece

Frontpage: machine model SH130

Subject to technical changes. Illustrations may show accessories that are not included in the standard version. Program update 10/2015

Terrot GmbH Paul-Gruner-Straße 72B 09120 Chemnitz Germany

Phone: +49 371 5201-0 | Fax: +49 371 5201-200

email: info@terrot.de | www.terrot.de